

## VoIP SOLUTIONS MODELO 5520 TELEFONO IP SECRETARIAL

ANSEL DISEÑA Y FABRICA LA MAYOR GAMA DE EQUIPOS VOIP. EL 5520 ES UN TELÉFONO IP DE ALTO PERFORMANCE.

FUNCIONES SOBRESALIENTES:

	/ G.729A/G.729B CODEC ALGORITHM
<ul style="list-style-type: none"> <li>• IDEAL PARA CONFERENCE CALL</li> </ul>	<ul style="list-style-type: none"> <li>• LCD DISPLAY: DIAL DATA_CALLER NAME _CALLER NUMBER AND SO ON</li> </ul>
<ul style="list-style-type: none"> <li>• PUEDE REGISTRAR 3 CUENTAS SIP DE MANERA SIMULTÁNEA</li> </ul>	<ul style="list-style-type: none"> <li>• VOLUMEN ADJUSTABLE PARA HANDSET AND SPEAKER</li> </ul>
<ul style="list-style-type: none"> <li>• FUNCIONES FORWARD/ BUSY FORWARD/ NO ANSWER</li> </ul>	<ul style="list-style-type: none"> <li>• SETTINGS POR HTTP WEB BROWSER</li> </ul>
<ul style="list-style-type: none"> <li>• LUZ DE MENSAJE EN COMBINACIÓN CON EL PBX IP</li> </ul>	<ul style="list-style-type: none"> <li>• VPN SOPORTA PPTP (OPCIONAL)</li> </ul>
<ul style="list-style-type: none"> <li>• AVISO DE LLAMADA ENTRANTE</li> </ul>	<ul style="list-style-type: none"> <li>• SOPORTA ASTERISK OPEN SOURCE IP PBX</li> </ul>
<ul style="list-style-type: none"> <li>• CONFERENCE CALL: 3-WAY CALL</li> </ul>	<ul style="list-style-type: none"> <li>• SOPORTA IP PBX</li> </ul>
<ul style="list-style-type: none"> <li>• FUNCION SPEED DIAL</li> </ul>	<ul style="list-style-type: none"> <li>• SPEED DIAL:10</li> </ul>
<ul style="list-style-type: none"> <li>• CALL WAITING</li> </ul>	<ul style="list-style-type: none"> <li>• DIAL PLAN SETTING</li> </ul>
<ul style="list-style-type: none"> <li>• AGENDA TELEFÓNICA PARA 140 NÚMEROS</li> </ul>	<ul style="list-style-type: none"> <li>• SOPORTA HOTLINE SETTING</li> </ul>
<ul style="list-style-type: none"> <li>• CALL FORWARD: ALL FORWARD/ BUSY FORWARD/ NO ANSWER FORWARD BLOCK SETTING: ALL/ BY TIME/ DURATION.</li> </ul>	<ul style="list-style-type: none"> <li>• SOPORTA ALARM SETTING</li> </ul>
<ul style="list-style-type: none"> <li>• AJUSTE PARA VOLUMEN</li> </ul>	<ul style="list-style-type: none"> <li>• LAN INTERFACE: 10MBPS/100MBPS</li> </ul>
<ul style="list-style-type: none"> <li>• 4 TIPO DE TONOS</li> </ul>	<ul style="list-style-type: none"> <li>• WAN INTERFACE : 10MBPS/100MBPS</li> </ul>
<ul style="list-style-type: none"> <li>• SUPORTA SIP PROTOCOL</li> </ul>	<ul style="list-style-type: none"> <li>• FUENTE DE PODER: INPUT_100-240V /50/60HZ, OUTPUT_DC12V /1A</li> </ul>
<ul style="list-style-type: none"> <li>• UPGRADE POR FTP/TFTP/HTTP SOPORTA AUTO PROVISION BY FTP/TFTP/HTTP</li> </ul>	<ul style="list-style-type: none"> <li>• US/EURO/UK/AUSTRALIAN STYLE AVAILABLE.</li> </ul>
<ul style="list-style-type: none"> <li>• SUPORTA G.711/ G.723.1 / G.726</li> </ul>	<ul style="list-style-type: none"> <li>• PHONE BODY COLOR: BLACK</li> </ul>
	<ul style="list-style-type: none"> <li>• LCD SIZE: 2 X 16</li> </ul>
	<ul style="list-style-type: none"> <li>• OPERATIONAL TEMPERATURE: 0 TO +40°C</li> </ul>
	<ul style="list-style-type: none"> <li>• STORAGE TEMPERATURE: -10 TO +50°C</li> </ul>
	<ul style="list-style-type: none"> <li>• RELATIVE HUMIDITY: 10-90% NON-</li> </ul>

CONDENSING
• UNIT DIMENSIONS/WEIGHT: 23.5CM× 21CM× 8.8CM/ 0.8KG
• BOX DIMENSIONS/WEIGHT:33.8CM X 20.7CM X 7.4CM/0.4KG
• SHIPPING CARTON (10 PIECES)DIMENSIONS/ WEIGHT: 43CM×38.5CM×34.5CM/1KG
• COMPLIANCE: FCC/CE/LVD
• FUNCTION KEYS: 25 FUNCTION KEYS BESIDES STANDARD KEYS 0-9,#, _
• SIP V1 (RFC2543), V2(RFC3261)
• IP/TCP/UDP/RTP/RTCP
• IP/ICMP/ARP/RARP/SNTP
• TFTP CLIENT/DHCP CLIENT/ PPPOE CLIENT
• TELNET/HTTP SERVER
• DNS CLIENT
• VLAN SETTING
• DMZ SETTING
• VIRTUAL SERVER
• MAC CLONE SETTING
• RING TONE
• RING BACK TONE
• DIAL TONE
• BUSY TONE
• USER PROGRAMMING TONE
• VOLUME ADJUSTMENT
• SPEED DIAL, PHONE BOOK
• FLASH
• SPEAKER PHONE
• CPC (CALLING PARTY CONTROL)
• G.711: 64K BIT/S (PCM)
• G.723.1: 6.3K / 5.3K BIT/S
• G.726: 16K / 24K / 32K / 40K BIT/S (ADPCM)
• G.729A: 8K BIT/S (CS-ACELP)
• G.729B: ADDS VAD & CNG TO

G.729
• STATIC IP
• DHCP
• PPPOE
• VAD: VOICE ACTIVITY DETECTION
• CNG: COMFORTABLE NOISE GENERATOR
• LEC: LINE ECHO CANCELLER
• PACKET LOSS COMPENSATION
• ADAPTIVE JITTER BUFFER
• HTTP 1.1 BASIC/DIGEST AUTHENTICATION FOR WEB SETUP
• MD5 FOR SIP AUTHENTICATION (RFC2069/ RFC 2617)
• TOS FIELD
• CALL HOLD
• CALL WAITING
• CALL FORWARD
• CALLER ID
• 3-WAY CONFERENCE
• STUN
• WEB BROWSER
• CONSOLE/TELNET
• KEYPAD
• IN-BAND DTMF
• OUT-OF BAND DTMF
• SIP INFO
• REGISTRAR SERVER (THREE SIP ACCOUNT)
• OUTBOUND PROXY
• TFTP
• CONSOLE
• HTTP
• FTP
• AUTO FIRMWARE UPDATE
• GARANTÍA 1 AÑO CONTRA DEFECTOS DE FABRICACIÓN